

In the Claims:

1. (Cancel)

2. (Cancel)

3. (Currently Amended)     A variable valve lift mechanism for an engine, comprising:  
    a rocker arm for transmitting a cam movement to a stem end of a valve;  
    a rotating axle movement means for moving a rotating axle of said rocker arm on a  
    moving plane which is a plane perpendicular to said rotating axle of said rocker arm; and  
    a restricting means for restricting said rocker arm to prohibit the rocker arm from  
    moving along a longitudinal direction of said rocker,  
    wherein said rotating axle movement means comprises:  
    a sliding arm supported by said rocker arm so as to linearly slide on said moving  
    plane along said longitudinal direction of said rocker arm;  
    a moveable shaft rotatably supported by said sliding arm to function as a rotating axle  
    of said rocker arm; and  
    a sliding means for linearly sliding said moveable shaft along said longitudinal  
    direction of said rocker arm and, ~~The mechanism as defined in claim 2,~~ wherein said sliding  
    arm comprises:  
        a cam side protruder integrally formed at said rocker arm toward said cam; and  
        a valve side protruder integrally formed at said rocker arm toward said valve.

4. (Original)   The mechanism as defined in claim 3, wherein said restricting means comprises:  
    a roller rotatably secured at said cam side protruder to contact said cam; and  
    a roller guide for guiding said roller to linearly move to a direction perpendicular to said longitudinal direction of said rocker arm.

5. (Original)   The mechanism as defined in claim 4, wherein said roller guide has a plurality of guide rollers for reducing friction created by said roller when said roller is contacted by said guide rollers.

6. (Currently Amended) The mechanism as defined in claim 2 3, wherein said sliding means comprises:

- a hitching pin protruding along an axial direction of said moveable shaft;
- a cam plate with an oval hole for said hitching pin to linearly slide therein;
- a motor for rotating said cam plate so that said hitching pin inserted into the oval hole can linearly move along said longitudinal direction of said rocker arm; and
- a controller for controlling said motor in response to an operating condition of an engine.

7. (Currently Amended) The mechanism as defined in claim 2 3, wherein said movable shaft further comprises a guide shaft that is disposed within said movable shaft and mounted parallel with said sliding arm to guide any movement of said moveable shaft.